WaterMark

Level 1

Certificate of Conformity

Australian Certification Services Pty Ltd grants to the WaterMark User:

Oventrop GmbH & Co KG

Trading as Oventrop GmbH & Co KG

the right to use the WaterMark as shown above in conjunction with the Certificate No. on product/s as identified in the WaterMark Schedule and as listed on the WaterMark database www.abcb.gov.au/Product-Certification/WaterMark-Certification-Schemewhich have been shown to comply with the relevant Standard/s and level of certification referred to below. The WaterMark User is granted a licence to use the WaterMark subject to the rules governing the use of the WaterMark.

Product Type:	Recirculation Balancing Valves
Brand:	OVENTROP
Evaluated to:	WMTS 012:2016 In-line valves for use in plumbing water supply systems—Miscellaneous types metallic and nonmetallic

Issue Date	25th July 2017
Initial Issue Date:	30th November 2015
Expiry Date:	29th November 2020

Paul Greig
General Manager

Certificate No.: 23156

This certificate remains the property of Australian Certification Services Pty Ltd

WaterMark Level 1 certification is a conformity assessment scheme based on ISO Guide 67 (system 5)

AUSTRALIAN CERTIFICATION SERVICES

Australian Certification Services Pty Ltd ABN 37 121 022 366
PO Box 627 Jannali, NSW 2226 AUSTRALIA
Phone:+61 2 8521 0726 Email:admin@certificationservices.com.au
www.certificationservices.com.au

JAS-ANZ
www.jas-anz.org/register

Certificate Number: 23156
Issue Date: 25th July 2017
Issue: 01 Revision: 01

WaterMark Certification Schedule

The WaterMark User	Oventrop GmbH & Co KG Paul- Oventrop-Strabe 1 Olsberg D-59939 Germany www.oventrop.de
Certificate Number	23156
Level of Certification	WaterMark Level 1
Certification Standards:	WMTS 012:2016 In-line valves for use in plumbing water supply systems—Miscellaneous types metallic and nonmetallic

Product Listing

Model Identification	Model Name	Brand Name	Product Description
420 81 04	Aquastrom C	OVENTROP	DN15 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Included Thermometer and Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP1/2"x RP1/2")
420 81 06	Aquastrom C	OVENTROP	DN20 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Included Thermometer and Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP3/4"x RP3/4")
420 81 08	Aquastrom C	OVENTROP	DN25 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Included Thermometer and Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP1"x RP1")
420 81 10	Aquastrom C	OVENTROP	DN32 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Included Thermometer and Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP1 1/4"x RP1 1/4")
420 81 52	Aquastrom C	OVENTROP	DN15 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP1/2"x RP1/2")
420 81 54	Aquastrom C	OVENTROP	DN20 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP3/4"x RP3/4")

AUSTRALIAN CERTIFICATION SERVICES

Australian Certification Services Pty Ltd ABN 37 121 022 366
PO Box 627 Jannali, NSW 2226 AUSTRALIA
Phone:+61 2 8521 0726 Email:admin@certificationservices.com.au
www.certificationservices.com.au

www.jas-anz.org/register

Certificate Number: 23156
Issue Date: 25th July 2017
Issue: 01 Revision: 01

Model Identification	Model Name	Brand Name	Product Description
420 81 56	Aquastrom C	OVENTROP	DN25 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP1"x RP1")
420 81 58	Aquastrom C	OVENTROP	DN32 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP1 1/4"x RP1 1/4")
420 85 04	Aquastrom C	OVENTROP	DN15 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Included Thermometer Sampling Valve and Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP1/2"x RP1/2")
420 85 06	Aquastrom C	OVENTROP	DN20 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Included Thermometer Sampling Valve and Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP3/4"x RP3/4")
420 85 08	Aquastrom C	OVENTROP	DN25 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Included Thermometer Sampling Valve and Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP1"x RP1")
420 85 10	Aquastrom C	OVENTROP	DN32 PN25 Metallic (Bronze) Bodied Balancing Valve (2 Scale Presetting Indicator) with Included Thermometer Sampling Valve and Blind Plugs (G1/4") Max. Temp. 90˚C Female Threaded Ends (RP1 1/4"x RP1 1/4")

AUSTRALIAN CERTIFICATION SERVICES

Australian Certification Services Pty Ltd ABN 37 121 022 366
PO Box 627 Jannali, NSW 2226 AUSTRALIA
Phone:+61 2 8521 0726 Email:admin@certificationservices.com.au
www.certificationservices.com.au

www.jas-anz.org/register

Certificate Number: 23156
Issue Date: 25th July 2017
Issue: 01 Revision: 01